

HAMA FlashPen Hook-Style USB 2.0 32GB (Product code: XWN-1096)**Price: 0 €****Technical specifications:**

Capacity:

- Maišytuvo indo dydis: 1,75 l
- Maišytuvo ąsočio darbinė talpa: 1,0 l
- Dubens talpa: 2,1 l
- Dubens maks. darbinė talpa: 1,5 l (sausų produktų / skysčių)
- Dubens maks. darbinė talpa.: 500 g (miltų)
- Produkto dydis (ilgis x plotis x aukštis) / 4.5L / 2.5 L talpykla vaisių minkštimams / 250 lapų / 2 L, tirščių indas: 1,2 L, Didelės talpos sulčių indas: 800 ml / New sessions per second : 40000 | Connection / user qty : 500000 | DPI connections : 250000 | Maximum number of access points : 64 | VPN tunnels (site-to-site) : 1500 | IPSec VPN connections : 500 | SSL VPN users : 2 | Virtual interfaces (VLANs) : 51 / 4L / 1 L vandens talpykla / 2 L (naudojama talpa 1.75 L) / 500 GB / 1000AV (On Battery) 500VA (Surge Protection outlets) / 1.5 litres
- Maišytuvo indo dydis: 1,75 l
- Maišytuvo ąsočio darbinė talpa: 1,0 l
- Dubens talpa: 2,1 l
- Dubens maks. darbinė talpa: 1,5 l (sausų produktų / skysčių)
- Dubens maks. darbinė talpa.: 500 g (m / New sessions per second : 40000 | Connection / user qty : 500000 | DPI connections : 250000 | Maximum number of access points : 64 | VPN tunnels (site-to-site) : 1500 | IPSec VPN connections : 500 | S / New sessions per second : 90000 | Connection / user qty : 1000000 | DPI connections : 600000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 6000 | IPSec VPN connections : 2000 | / New sessions per second : 40000 | Connection / user qty : 500000 | DPI connections : 250000 | Maximum number of access points : 64 | VPN tunnels (site-to-site) : 1500 | IPSec VPN connections : 500 | S / New sessions per second : 60000 | Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 60000 | Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 60000 | Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 90000 | Connection / user qty : 1000000 | DPI connections : 600000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 6000 | IPSec VPN connections : 2000 | / New sessions per second : 90000 | Connection / user qty : 1000000 | DPI connections : 600000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 6000 | IPSec VPN connections : 2000 | /
- Maišytuvo indo dydis: 1,75 l
- Maišytuvo ąsočio darbinė talpa: 1,0 l
-

Dubens talpa: 2,1 l • Dubens maks. darbinė talpa: 1,5 l (sausų produktų / skysčių) • Dubens maks. darbinė talpa.: 500 g (m / New sessions per second : 40000 | Connection / user qty : 500000 | DPI connections : 250000 | Maximum number of access points : 64 | VPN tunnels (site-to-site) : 1500 | IPSec VPN connections : 500 | S / New sessions per second : 90000 | Connection / user qty : 1000000 | DPI connections : 600000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 6000 | IPSec VPN connections : 2000 | / New sessions per second : 40000 | Connection / user qty : 500000 | DPI connections : 250000 | Maximum number of access points : 64 | VPN tunnels (site-to-site) : 1500 | IPSec VPN connections : 500 | S / New sessions per second : 60000 | Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 60000 | Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 60000 | Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 90000 | Connection / user qty : 1000000 | DPI connections : 600000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 6000 | IPSec VPN connections : 2000 | / New sessions per second : 90000 | Connection / user qty : 1000000 | DPI connections : 600000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 6000 | IPSec VPN connections : 2000 | / Maišytuvo indo dydis: 1,75 l • Maišytuvo ąsočio darbinė talpa: 1,0 l • Dubens talpa: 2,1 l • Dubens maks. darbinė talpa: 1,5 l (sausų produktų / skysčių) • Dubens maks. darbinė talpa.: 500 g (m / New sessions per second : 40000 | Connection / user qty : 500000 | DPI connections : 250000 | Maximum number of access points : 64 | VPN tunnels (site-to-site) : 1500 | IPSec VPN connections : 500 | S / New sessions per second : 90000 | Connection / user qty : 1000000 | DPI connections : 600000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 6000 | IPSec VPN connections : 2000 | / 4 trikampiai sumuštiniai vienu metu / 500 lapų įpakavime, dėžėje 5 pak. / New sessions per second : 40000 | Connection / user qty : 500000 | DPI connections : 250000 | Maximum number of access points : 64 | VPN tunnels (site-to-site) : 1500 | IPSec VPN connections : 500 | S / New sessions per second : 60000 | Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 60000 | Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 90000 | Connection / user qty : 1000000 | DPI connections : 600000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 6000 | IPSec VPN connections : 2000 | / Daypack mode: One DSLR with lens attached, 1-2 extra lenses, a flash unit, accessories(memory cards, cables, battery and charger), tripod or monopod,stick and tablet. / • Maišytuvo indo dydis: 1,75 l • Maišytuvo ąsočio darbinė talpa: 1,0 l • Dubens talpa: 2,1 l • Dubens maks. darbinė talpa: 1,5 l (sausų produktų / skysčių) • Dubens maks. darbinė talpa.: 500 g (m / New sessions per second : 40000 | Connection / user qty : 500000 | DPI connections : 250000 | Maximum number of access points : 64 | VPN tunnels (site-to-site) : 1500 | IPSec VPN connections : 500 | S / New sessions per second : 90000 | Connection / user qty : 1000000 | DPI connections : 600000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 6000 | IPSec VPN connections : 2000 | / New sessions per second : 40000 |

Connection / user qty : 500000 | DPI connections : 250000 | Maximum number of access points : 64 | VPN tunnels (site-to-site) : 1500 | IPSec VPN connections : 500 | S / New sessions per second : 60000 |
 Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 60000 |
 Connection / user qty : 750000 | DPI connections : 500000 | Maximum number of access points : 96 | VPN tunnels (site-to-site) : 4000 | IPSec VPN connections : 2000 | / New sessions per second : 60000 |
 Connection / user qty : 750000 | DPI connections : 500000 | Maximum

Intel® H170 chipset : 6 x USB 2.0/1.1 port(s) (2 at back panel, black, Type-A, 4 at mid-board); Intel® H170 chipset : 6 x USB 3.0/2.0 port(s) (2 at back panel, blue, Type-A, 4 at mid-board); Intel / Intel® Z170 chipset : 6 x USB 3.0 port(s) (2 at back panel, blue, 4 at mid-board); Intel® Z170 chipset : *3 8 x USB 2.0 port(s) (4 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 contro / Intel® B85 chipset : 4 x USB 3.0 port(s) (2 at back panel, blue, 2 at mid-board); Intel® B85 chipset : 6 x USB 2.0 port(s) (2 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 controller : 1 / Intel® B150 chipset : 1 x USB 5Gb/s port(s) port(s) (1 at back panel, , Reversible, Support 3A power output); Intel® B150 chipset : 4 x USB 3.0/2.0 port(s) (2 at back panel, blue, 2 at mid-board); / Intel Z170 Chipset: 8 x USB 3.0 prievadai (4 viduryje), Intel Z170 Chipset: * 4, 4 x USB 2.0 prievadai, Intel USB 3.1 kontroleris: 2 x USB 3.1 prievadai (2 ant galinio skydelio, A + C tipu), AS / Intel Z170: 6 x USB 3.0 prievadas (-ai) (2 ant galinio skydelio, mėlyna, 4 viduryje), Intel Z170: 6 x USB 2.0 prievadas (-ai) (2 ant galinio skydelio, 4 viduryje), Intel USB 3.1 kontroleris: 1 / 6 x USB 3.0/2.0 port(s) (2 galiniame skydelyje, mėlyni, 4 viduryje), 8 x USB 2.0/1.1 port(s) (4 galiniame skydelyje, juodi, 4 viduryje), 1 x USB 3.1/3.0/2.0 port(s) (1 galiniame skydelyje, mėlyna, / ASMedia® ASM1042 controller : 2 x USB 3.0/2.0 port(s) (2 at back panel, blue); AMD A68H FCH (Bolton D2H) chipset : 6 x USB 2.0/1.1 port(s) (2 at back panel, , 4 at mid-board); AMD A68H FCH (Bo / Intel® H110 chipset: 4 x USB 3.0/2.0 port(s) (2 at back panel, blue, 2 at mid-board); Intel® H110 chipset: 6 x USB 2.0/1.1 port(s) (2 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 contro / Intel® Z170 chipset: 6 x USB 3.0/2.0 port(s) (2 at back panel, blue, 4 at mid-board); Intel® Z170 chipset: 8 x USB 2.0/1.1 port(s) (4 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 contro / Intel® H170 chipset: 1 x USB 5Gb/s port(s) port(s) (1 at back panel, , Type-C, Reversible, Support 3A power output); Intel® H170 chipset: 6 x USB 3.0/2.0 port(s) (2 at back panel, blue, Type-A, 4 at / Intel® B150 chipset : 1 x USB 5Gb/s port(s) port(s) (1 at back panel, , Reversible, Support 3A power output); Intel® B150 chipset : 4 x USB 3.0/2.0 port(s) (2 at back panel, blue, 2 at mid-board); / Intel® B150 chipset : 6 x USB 2.0/1.1 port(s) (2 at back panel, black, Type-A, 4 at mid-board); Intel® B150 chipset : 5 x USB 3.0/2.0 port(s) (3 at back panel, blue, Type-A, 2 at mid-board); Intel / Intel® Z170 chipset : 8 x USB 3.0 port(s) (6 at back panel, blue, 2 at mid-board); Intel® Z170 chipset : 4 x USB 2.0 port(s) (4 at mid-board); ASMedia® USB 3.1 controller : 1 x USB 3.1 port(s) (1 / ASMedia® USB 3.1 controller : 1 x USB 3.1 port(s) (1 at back panel, , Type-A); ASMedia® USB 3.1 controller : 1 x USB 3.1 port(s) (1 at back panel, , Type-C, Reversible); Intel® H170 chipset : 6 x / Intel® Z170 chipset : 6 x USB 3.0 port(s) (2 at back panel, blue, 4 at mid-board); Intel® Z170 chipset : 8 x USB 2.0 port(s) (4 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 controller : / Intel® Z170 chipset : 5 x USB 3.0/2.0 port(s) (1 at back panel, blue, Type-A, 4 at mid-board); Intel® Z170 chipset : 5 x USB 2.0/1.1 port(s) (1 at back panel, black, Type-A, 4 at mid-board); A / ASMedia® USB 3.1 controller : 2 x USB 3.1/3.0/2.0 port(s) (2 at back panel, teal blue); Intel® Z170 chipset : 1 x USB 5Gb/s port(s) port(s) (1 at back panel, , Type-C, Reversible, Support 3A pow / Intel® Z170 chipset : 6 x USB 2.0/1.1 port(s) (2 at back panel, black, Type-A, 4 at mid-board); Intel® Z170 chipset : 6 x USB 3.0/2.0 port(s) (2 at back panel, blue, Type-A, 4 at mid-board); I / Intel® Z170 chipset : 6 x USB 3.0/2.0 port(s) (2 at back panel, blue, 4 at mid-board); Intel® Z170 chipset : 6 x USB 2.0/1.1 port(s) (2 at back panel, , 4 at

USB support:

mid-board); ASMedia® USB 3.1 contr / ASMedia® USB 3.1 controller : 1 x USB 3.1 port(s) (Type-A); ASMedia® USB 3.1 controller : 1 x USB 3.1 port(s) (Type-C, Reversible); Intel® Z170 chipset : 6 x USB 3.0/2.0 port(s) (4 at back p / ASMedia® USB 3.1 controller : 1 x USB 3.1/3.0/2.0 port(s) (1 at back panel, teal blue, Type-A) ASMedia® USB 3.1 controller : 1 x USB 3.1 port(s) (1 at back panel, black, Type-C) Intel® B85 chips / Intel® H170 chipset : 6 x USB 2.0/1.1 port(s) (2 at back panel, black, Type-A, 4 at mid-board); Intel® H170 chipset : 6 x USB 3.0/2.0 port(s) (2 at back panel, blue, Type-A, 4 at mid-board); Intel / Intel® Z170 chipset : 6 x USB 3.0 port(s) (2 at back panel, blue, 4 at mid-board); Intel® Z170 chipset : *3 8 x USB 2.0 port(s) (4 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 contro / Intel® B85 chipset : 4 x USB 3.0 port(s) (2 at back panel, blue, 2 at mid-board); Intel® B85 chipset : 6 x USB 2.0 port(s) (2 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 controller : 1 / Intel® B150 chipset : 1 x USB 5Gb/s port(s) port(s) (1 at back panel, , Reversible, Support 3A power output); Intel® B150 chipset : 4 x USB 3.0/2.0 port(s) (2 at back panel, blue, 2 at mid-board); / Intel Z170 Chipset: 8 x USB 3.0 prievadai (4 viduryje), Intel Z170 Chipset: * 4, 4 x USB 2.0 prievadai, Intel USB 3.1 kontroleris: 2 x USB 3.1 prievadai (2 ant galinio skydelio, A + C tipų), AS / Intel Z170: 6 x USB 3.0 prievadas (-ai) (2 ant galinio skydelio, mėlyna, 4 viduryje), Intel Z170: 6 x USB 2.0 prievadas (-ai) (2 ant galinio skydelio, 4 viduryje), Intel USB 3.1 kontroleris: 1 / 6 x USB 3.0/2.0 port(s) (2 galiniame skydelyje, mėlyni, 4 viduryje), 8 x USB 2.0/1.1 port(s) (4 galiniame skydelyje, juodi, 4 viduryje), 1 x USB 3.1/3.0/2.0 port(s) (1 galiniame skydelyje, mėlyna, / ASMedia® ASM1042 controller : 2 x USB 3.0/2.0 port(s) (2 at back panel, blue); AMD A68H FCH (Bolton D2H) chipset : 6 x USB 2.0/1.1 port(s) (2 at back panel, , 4 at mid-board); AMD A68H FCH (Bo / Intel® H110 chipset: 4 x USB 3.0/2.0 port(s) (2 at back panel, blue, 2 at mid-board); Intel® H110 chipset: 6 x USB 2.0/1.1 port(s) (2 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 contro / Intel® Z170 chipset: 6 x USB 3.0/2.0 port(s) (2 at back panel, blue, 4 at mid-board); Intel® Z170 chipset: 8 x USB 2.0/1.1 port(s) (4 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 contro / Intel® H170 chipset: 1 x USB 5Gb/s port(s) port(s) (1 at back panel, , Type-C, Reversible, Support 3A power output); Intel® H170 chipset: 6 x USB 3.0/2.0 port(s) (2 at back panel, blue, Type-A, 4 at / Intel® B150 chipset : 1 x USB 5Gb/s port(s) port(s) (1 at back panel, , Reversible, Support 3A power output); Intel® B150 chipset : 4 x USB 3.0/2.0 port(s) (2 at back panel, blue, 2 at mid-board); / Intel® B150 chipset : 6 x USB 2.0/1.1 port(s) (2 at back panel, black, Type-A, 4 at mid-board); Intel® B150 chipset : 5 x USB 3.0/2.0 port(s) (3 at back panel, blue, Type-A, 2 at mid-board); Intel / Intel® Z170 chipset : 8 x USB 3.0 port(s) (6 at back panel, blue, 2 at mid-board); Intel® Z170 chipset : 4 x USB 2.0 port(s) (4 at mid-board); ASMedia® USB 3.1 controller : 1 x USB 3.1 port(s) (1 / ASMedia® USB 3.1 controller : 1 x USB 3.1 port(s) (1 at back panel, , Type-A); ASMedia® USB 3.1 controller : 1 x USB 3.1 port(s) (1 at back panel, , Type-C, Reversible); Intel® H170 chipset : 6 x / Intel® Z170 chipset : 6 x USB 3.0 port(s) (2 at back panel, blue, 4 at mid-board); Intel® Z170 chipset : 8 x USB 2.0 port(s) (4 at back panel, black, 4 at mid-board); ASMedia® USB 3.1 controller : / Intel® Z170 chipset : 5 x USB 3.0/2.0 port(s) (1 at back panel, blue, Type-A, 4 at mid-board); Intel® Z170 chipset : 5 x USB 2.0/1.1 port(s) (1 at back panel, black, Type-A, 4 at mid-board); A / ASMedia® USB 3.1 controller : 2 x USB 3.1/3.0/2.0 port(s) (2 at back panel, teal blue); Intel® Z170 chipset : 1 x USB 5Gb/s