



## Technical specifications:

USB wireless receiver / microUSB - USB / 1 x USB - 4 pinų USB A-tipo / XFP / CX4 / Gold-plated USB connector / USB siųstuvas / PS/2 / The SAS Cable is a serial link that creates a point-to-point connection between devices / Wireless / 1 x SFP+ - male. Other side 1 x SFP+ - male / PCIe lanes (to system); SAS links, 2x4 internal (to device) / Belaidė / USB jungtis PC, Mac ir PS4. / HD-Mini to HD-Mini SAS / Universal 3.5mm plug / USB, 3.5 mm / 3.5 mm lizdas / Plastic / Metal / USB jungtis / 3,5 mm paausutas stereo mini / USB jungtis arba Bluetooth sąsaja / USB, / USB port or Bluetooth® / LC Fiber Optic /

Port type: Removable Mini-USB 2.0; Braided 1.8 m / GU10 / E14 / RJ45 / Dual LC / USB, removable cable / USB 2.0 Full Speed, 1.8m length cable / 3.5mm / E27 / RJ45 - RJ45 / 3.5 mm jack / 3.5 mm / PC with USB port / USB (2.0/3.0) / USB (2.0 / 3.0) / USB cable: 1.8m, braided, gold plated, removable / Wired, USB / 3.5 mm stereo jungtis ausinėms / Dell PERC H310 Integrated RAID Controller, Mini-Type - Kit / Dell PERC H310 Integrated RAID Controller, Full Height Adapter - Kit / Bluetooth® v3.0 / Hi-Speed USB 2.0 / USB Dongle / USB Mini reciever / USB 2.0 / USB Port / 1 x USB - 4 pin USB Type A / USB / RJ-45 / USB and PS/2 (USB-to-PS/2 adaptor). / LC / Duplex LC

Focal Length (mm):

Aperture:

Filter size (mm): 87 / 74 / 35 / 34 / 42 / 46 / 43 / 86 / 95 / 105 / 82 / 49 / 62 / 77 / 72 / 40,5 / 40,5 / 40,5 / 37 / 55 / 52 / 67 / 58

Type of sensor: Photoelectric / photo optical / Photoelectric / Thermal / Optoelectronic / Laser / Optical / Nikon CX / Q sensor / Micro FourThirds / Full Frame / FT (FourThirds) / APS-C / Full Frame / APS-C

Image stabilisation:

Lens type:

Židinio nuotolis: